

## 2600+



*Tally*  
DASCOM

The Tally Dascom T2600+ is a highly featured, reliable and stylish machine. Performance and workload, ergonomics, maintainability, excellent price - everything has been incorporated to ensure it is the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in a reliable paper transportation, even on 6-part stock. Loading the paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors.

### Highlights at a Glance:

- Print Speeds up to 680 cps
- 20,000 Pages per Month Workload
- 80 Columns
- 24 pin Print Head produces excellent print quality
- **Straight through paper path** for easy forms loading
- Ethernet, Parallel and USB interfaces standard
- LCD Display

User intervention is kept at a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, or in the office. An unobtrusive 52 dbA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

### Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service bar code standard will require this capability to take advantage of the best rates available.

Intelligent Mail Barcode sample



## Configuration

2600+ Standard Configuration

SERIAL MATRIX  
PRINTERS

MOBILE  
PRINTERS

FLATBED  
PRINTERS

THERMAL  
PRINTERS

CONNECTIVITY




CONSUMABLES

SERVICE

## 2600+

<b>Print Speed</b>	680 cps (Fastest Draft); 500 cps (HS-Draft), 333 cps (Draft), 111 cps (LQ) at 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Print Head Life</b>	500 million dots per wire
<b>Memory</b>	256 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100 BaseT)
<b>Optional Connectivity</b>	Serial RS-232
<b>Standard Emulation</b>	IBM ProPrinter XL24, Epson ESC/P2, MTPL + Barcode + LCP
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing
<b>Consumable</b>	Ribbon: 9 million characters
<b>Standard Paper Handling</b>	One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off
<b>Optional Paper Handling</b>	Additional push tractor (rear),
<b>Number of Copies</b>	Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copies
<b>Paper Type</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 76 to 278 mm, 3.0 to 11.0 in; Length: 76 to 599 mm, 3.0 to 23.6 in
<b>Physical Weight</b>	8,6 kg, 18.9 lbs
<b>Physical Size</b>	458 x 265 x 200 mm, 18.0 x 10.4 x 7.9 in (W x D x H)
<b>Acoustic</b>	52 dB(A)
<b>Power Voltage</b>	100 - 240 V wide range auto-sensing
<b>Power Consumption</b>	40 Watt Printing; <10 W Sleep Mode
<b>Temperature</b>	+10° to +40° C; 10% to 85% humidity
<b>Workload</b>	20.000 pages per month
<b>MTBF</b>	15.000 hours
<b>Drivers</b>	Windows 2000/XP/Vista/7/8/10 and Server 2003/2008; SAP
<b>Warranty</b>	One year return to depot

**DASCOM Americas**  
 34 Lakeview Court  
 Verona, Virginia 24482  
 Tel: (877) 434-1377  
[www.dascomamericas.com](http://www.dascomamericas.com)

SERIAL MATRIX PRINTERS   
 MOBILE PRINTERS   
 FLATBED PRINTERS   
 THERMAL PRINTERS 