

CLI AG7000 Series Thin Client



Everything You Need to get the Job Done

CLI's AG7000 raises the bar with this SOC device offering the ideal fit as your endpoint for your desktop virtualization. With a quad core....this unit can handle the most complex VDI environment. No matter how demanding your virtualization setting, the AG7000 can fulfill those requirements with features such as 6 USB ports, Display port, DVI-I port as well as 802.11n wireless option and much more. The impressive performance along with simplicity of deployment makes the AG7000 the perfect choice for your desktop whether you are utilizing Microsoft, Citrix or VMware as your solution.

Value Without Compromise

The AG7000 offers multiple operating system options, including Linux, WES7 and W10IoT. Terminal Emulation with the included TermPro rounds out the software providing support for both VDI as well as IBM environments. This is the flexibility that customers demand and with the ability to centrally manage your CLI devices with Device Manager, simplicity of deployment and management becomes a reality.

At a Glance

The AG7000 is the ideal client for complex environments that fit within today's budgets. With support for the latest OS offerings from Microsoft and CLI LX3 Linux the AG7000 is ready for any deployment from legacy terminal emulation to virtualized environments.

Features

- Quad core AMD A6 1.2 GHz processor
- Dual Digital Video (DisplayPort and DVI-I).
- Dedicated Radeon HD R4 GPU.
- Multiple mounting options.
- Optional internal wireless.
- Energy efficient, robust feature set, maximum performance.



CLI AG7000 Universal Client

Modular logic unit, AMD A6 Micro-AT6500T (1.2 GHz) SOC Quad Core CPU, Gigabit Ethernet, 6 US B ports, audio in/out ports, external power supply, socketed DR AM and Industrial grade SSD Flash, security lock slot, USB optical mouse, USB US 104-key keyboard, US power cord, per seat license for CLI Device Manager software, three-year return-to depot warranty.

| FEATURES | DESCRIPTION | AG7000W10 | AG7000W | AG7000L |
|-------------------------------------|--|----------------------------------|-------------|-----------|
| Operating System | Customize your AG7000 with Windows® Embedded Standard or Linux Operating Systems. Contact Your Reseller or CLI Sales Representative for Custom Operating System Configuration. | WES7 64-bit Windows 10 IoT | WES7 64-bit | Linux LX3 |
| Processor | AMD A6 Micro-AT6500T (1.2 GHz) SOC Quad Core Processor | | | |
| Chipset | AMD A-Series | | | |
| Video | AMD Radeon™ R4 Graphics Up to 4K on DP and 2560 x 1600 with two monitors DVI + DP Wide Screen Support, 32-bit Color (1) Display Port, (1) DVI-I Port (VGA Adapter Included) | | | |
| Flash | SATA SSD Flash Module | 32GB | 16GB | 16GB |
| Memory | (1) DDR3L - 1333 SODIMM | 4GB | 4GB | 2GB |
| Communications | (1) Gigabit Ethernet Port | | | |
| Wireless | Optional Integrated Mini PCIe Internal Wireless 802.11b/g/n Wi-Fi™ with Dual Internal Antenna | AG7060W10 | AG7060W | AG7060L |
| CLI TermPro (Terminal Emulation) | TermPro Supports TN5250 (IBM AS/400), TN3270, (IBM Mainframe), VT100, Wyse 60 and other ASCII (Unix/Linux Systems) Emulation Sessions with One or More Hosts. Enhanced User Interface (TN5250 Display Only), Support for 122-Key keyboard, & TCP/IP. | | | |
| Ports and Connectors | (4) USB 2.0 Ports (Rear), (2) USB 3.0 Ports (Front), (1) DisplayPort, (1) DVI-I, (1) RJ-45/Ethernet, (1) Mic-In Jack, (1) Audio Out Jack, (1) Micro SD Card Reader | | | |
| Mounting Hardware | Standard: VESA 100mm Compliant Mounting Holes (Mounting Screws Included), Vertical Stand, Horizontal Feet. | | | |
| Power Supply | Auto Sensing 100 – 240 VAC, 50/60Hz, Max 15 Watt | | | |
| Protocols | Microsoft® RDC/RemoteFX®, Citrix ICA/HDX®, VMware Horizon View®, Web Browser, Telnet, TCP/IP with DNS, XDMCP, DHCP, PPP, and PXE | | | |
| Remote Management | Device Manager Remote Configuration, Image Updates, Asset Management, Shadowing (License Purchase Required), Image Update and Recovery with USB Drive Supported | | | |
| Weight | 1.7 lbs. | | | |
| Dimensions | (w x d x h) 8.2 in x 5.7 in x 1.4 in | | | |
| Temperature & Humidity | 5 °C to 40 °C 20% to 80% Non-Condensing Humidity | | | |
| Safety Certifications | RoHS, FCC Class B, VCCI, UL, CE | | | |
| Warranty | Limited Three Year Hardware Warranty, Optional Three Year Advanced Replacement Warranty | | | |

CLI, Inc. 735 Challenger Street, Brea, CA 92821

info@computerlab.com | 1 800-727-5250 | www.computerlab.com

©2017 CLI, Inc. All rights reserved. Specifications are subject to change without notice. CLI is a registered trademark. All other trademarks are the property of their respective owners. CLI shall not be liable for technical or editorial errors or omissions contained herein.

